

PRODUCT DIMENSIONS

EVERLAST Rolls	Thickness	Weight (lbs./sq. ft.)	
48" width	6 mm (1/4")	1.25	
48" width	9 mm (3/8")	1.95	
EVERLAST Tiles	Coverage (sq. ft./tile)	Weight (lbs./sq. ft.)	Weight (lbs./tile)
36" x 36" x 6 mm (1/4")	9.0	1.25	11.25
36" x 36" x 9 mm (3/8")	9.0	1.95	17.55
EVERLAST UltraTile	Coverage (sq. ft./tile)	Weight (lbs./sq. ft.)	Weight (lbs./tile)
24" x 24" x 25 mm (1")	4	4	16
EVERLAST UltraTile Reducer	Coverage (linear ft.)	Weight (lbs./pc.)	
48" x 4" x 1"	4	5	

PHYSICAL DATA TEST

	ASTM	EVERLAST SBR Rubber	UltraTile
Tensile Strength	D412	200 lb/in ² min	200 lb/in ² min
Flexibility	F137	Pass 1/4 inch mandrel	N/A
Coefficient of Friction	D2047	>0.9	>0.9
Thermal Conductivity	C518	0.406 Btu-in/hr-ft ² -F	0.400 Btu-in/hr-ft ² -F (approx)
Static Load Limit	F970, 1,000 lbs.	<0.020 in	Not determined
Chemical Resistance	F925	No change	No change
Impact Insulation Class	E49	45 min	>50
Noise Reduction Coefficient	C423	0.10 Sabine/ft ²	0.10 Sabine/ft ²
Elongation at Break	D412	75% min	75% min

TECHNICAL INFORMATION

INSTALLATION – EVERLAST rolls, tiles and UltraTile have a range of installation methods, from easy “install with your own staff” techniques to more permanent and professionally installed full-spread adhesive systems. For more detailed installation recommendations, please request an EVERLAST Installation and Maintenance Manual. For information on outdoor installation, please call 1-888-383-7655.

ADHESIVE – ECORE developed E-Grip™ II, an easy-to-use one-part polyurethane adhesive, for adhering EVERLAST flooring to various substrates with moisture content up to 5.5 lbs. Only an ECORE approved adhesive should be used. E-Grip II's coverage is approximately 95 sq. ft./gal. (1/16" square notch trowel) depending on substrate conditions and is available in 2.5 or 5 gallon pails.

MAINTENANCE – For “Fundamentals” or “High Intensity” color applications, most installations require only routine vacuuming and wet mopping with clean water and mild detergent or pH neutral solution. For “Custom Logo” color applications – protective coating and regular upkeep will assure long-lasting appearance and resistance to normal wear and tear and foot traffic. Taski® floor care and maintenance products, available nationally, offer simple and reliable protection and performance. For more detailed information, please request an EVERLAST Installation and Maintenance Manual.

WARRANTY – All ECORE flooring is guaranteed by ECORE to be free from manufacturing defects on both material and workmanship. If such a defect is discovered, the customer must notify ECORE either through the contracting installer, distributor or directly. If found to be defective within three years under normal non-abusive conditions, the sole remedy against the seller will be the replacement or repair of the defective goods, or at the seller's option, credit may be issued not exceeding the selling price of the defective goods.